



"USP BULGARIA" LTD.
Bulgaria, Sofia
1582, jk "Druzha" 2
Blvd "Prof.Tsvetan Lazarov" № 90
+380503115715

Filler ALU

Polyester filler with aluminum powder having the tiled structure. It is used to remove heat from the problem areas are mainly on horizontal surfaces. Due to the low content of fillers can be easily applied in thin layers. The area of application should be wider than the layer of filling fillers to create the heat sink bridge. Is particularly relevant when using a dark varnish, as well as engines.



For professional use only

How to use: Apply the filler in the package thoroughly before use. Put the required amount on a clean and dry surface and mixed with the hardener in the ratio of 100 g filler to 2-3g. hardener.

Care should be taken within the mixing ratio, as when I change occurs or discoloration of the surface paint or tape the abrasive



Precautions: Contains Styrene. Flammable. Do not breathe vapor / spray. Harmful may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Avoid contact with skin. Wear suitable protective clothing, gloves and goggles or a face shield. Use only in well-ventilated areas. Avoid release to the environment, follow the instructions and safety data sheets. If swallowed, seek medical advice immediately and show this container or label.

Additional information	
Color	silver
Density	1,76kg/l
Neutral fillers	62%
Content	1,5kg