



"USP BULGARIA" LTD.
Bulgaria, Sofia
1582, jk "Druzhba" 2
Blvd "Prof.Tsvetan Lazarov" № 90
+380503115715

Universal filler Light&Soft

Filler Polystyrene filling comprises glass microspheres which have a low own weight. Perfectly polished, even after 3 days after curing. Putty is 35% lighter from the usual filling putty. Ideal for long-term maintenance or repair of the moving parts of a car.

WARNING: Overdose hardener may cause discoloration of the surface of varnish. It is not recommended to use the product at temperatures below 15 ° C.



For professional use only

Method of application: the foundation must be clean, dry and free of grease and matted. Putty weight should be well mixed with the curing agent in an amount of 2-3 % hardener and apply to the base for about 5 minutes at 20 ° C. A higher temperature will shorten the working life of the product and accelerates the process of curing.



Precautions: Contains Styrene. Flammable. Do not breathe vapor / spray. Harmful may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Avoid contact with skin. Wear suitable protective clothing, gloves and goggles or a face shield. Use only in well-ventilated areas. Avoid release to the environment, follow the instructions and safety data sheets. If swallowed, seek medical advice immediately and show this container or label.

More information	
Volume	1kg